

31 gr



Made under

ISO 14001

ISO 9001



>>Type of uses (*)

As protection against mechanical risks: projections of solids, of chips, particles, shocks ...
Grinding, industry, sport, laboratories, assembly shops. woodworking, polishing.
Protection against UV rays. Sun protection. Outdoor activities.

>> Technical features

Safety sunglasses.

- ✓ **Anti-scratch and anti-fog smoke polycarbonate lenses.**
- ✓ **Lens thickness:** 2.00 mm.
- ✓ **Nose bridge and inserts:** TPR.
- ✓ **Foam:** EVA.
- ✓ **Screws:** stainless steel.
- ✓ **Dimensions:** 135 mm (distance between screws).
- ✓ **Weight:** 31 grams.
- ✓ **Packing:** - Carton of 100 pairs.
- Box of 10 pairs.



Learn more: www.singer.fr

>> Advantages

- ✓ Ergonomic features giving a perfect fit of the equipment.
- ✓ Very stylish design.
- ✓ Foam delivers greater comfort and increased protection from dust, debris, and small particles.
- ✓ The **ISO 9001 / ISO 14001** certified production guarantees the reliability / regularity of the production and the control of the environmental impact.

>> Conformity

This product has been tested according to the following European Standards:

- ✓ **EN 166: 2001.** Personal eye-protection. Specifications.
- ✓ **EN 172 :1994/A1:2000/A2: 2002.** Personal eye-protection. Sunglare filters for industrial use.

It complies with the European **Regulation (EU) 2016/425** on Personal Protective Equipment (**PPE**). **Category II.**

EU type examination certificate (**module B**) issued by **CERTOTICCA**, notified body **n°0530**.



Mechanical protection (EN166)	Symbol F	Impact resistant against high speed particles (corresponds to the impact of a steel ball with a diameter of 6 mm and a minimum mass of 0.86 g launched at 45 m/s).
Optical quality (EN166)	Symbol 1	Class 1 continuous works (better quality).
Scale number (EN172)	Symbol 5-2	Use: recommended general filter for most uses. Designation (1): medium. The designation is not translated literally in various language versions of this standard since the filter «darkness» will be considered differently according to the intensity of light experience in the countries concerned.

Your distributor **SINGER® SAFETY**

SINGER®
safety