


29 g



>>Uses (*)

Thanks to its technical characteristics, this equipment is particularly suitable for all major works requiring protection against mechanical risks and projections including: grinding, carpentry, polishing, industry, laboratories, sports etc ...
UV protection.

>> Technical features

Safety spectacles.

Clear anti-fog polycarbonate lenses.

Polycarbonate frame.

Polycarbonate temple with

P.V.C non-slip pad.

✓ **Lens thickness:** 2.00 mm.

✓ **Pont de nez:** P.V.C souple.

✓ **Vis:** acier inoxydable.

✓ **Weight:** 29 g.

✓ **Packing:** - Carton of 100 pairs.

- Boxes of 10 pairs.

- Each goggle packed under individual polybag.



Learn more www.singer.fr

>> Advantages

- ✓ Ergonomic features giving a perfect fit of the equipment.
- ✓ Dynamic design.
- ✓ Light weight. Very comfortable wear.
- ✓ Reliability of an **ISO 9001** system in production.



>> Conformity

This product has been tested according to the following European Standards:

✓ **EN 166: 2001.** Personal eye-protection. Specifications.

✓ **EN 170: 2002.** Personal eye-protection. Ultraviolet filters. Transmittance requirements and recommended use.

It complies with the European **Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). **Category II.**

EU type examination certificate (**module B**) issued by **BSI** (Netherlands). Notified body **n°2797.**

Download the EU declaration of conformity on: <http://docs.singer.fr>



Mechanical protection (EN166)	Symbole FT	Impact resistant against high speed particles at high temperatures (corresponds to the impact of a steel ball with a diameter of 6 mm and a minimum mass of 0.86 g launched at 45 m/s).
Optical quality (EN166)	Symbole 1	Class 1 continuous works (better quality).
Scale number (EN170)	Symbole 2C.1.2	Colour perception: may be impaired unless marked «2C». Typical application: for use with sources which emit predominantly ultraviolet radiation at wavelengths shorter than 313 nm and when glare is not an important factor: this covers the UVC and most of the UVD Bands (b). Typical sources: Low pressure mercury lamps such as lamps used to stimulate fluorescence or «black lights», mercury lamps, germicidal lamps. (b) U.V.B: 280 nm to 315 nm et U.V.C: 100 nm to 280 nm.

Your distributor **SINGER® SAFETY**

SINGER® 
safety