


24 g



[Incredibly lightweight]



>> **Uses (*)**

Thanks to its technical characteristics, this equipment is particularly suitable for all major works requiring protection against mechanical risks and projections including: grinding, carpentry, polishing, industry, laboratories, sports etc ... UV protection.

>> **Technical features**

- ✓ Fashion and styling safety spectacle in clear polycarbonate and with protective sideshields.
- ✓ **Lens thickness:** around 2.00 mm.
- ✓ **Dimensions:** Length 160 mm. Width 135 mm.
- ✓ **Weight:** around 24 g.
- ✓ **Packing :** - Carton of 100 pairs.
- Box of 10 pairs.



Learn more: www.singer.fr

>> **Advantages**

- ✓ Extremely lightweight and modern safety eyewear.
- ✓ Outstanding field of vision and exceptional protection.
- ✓ Molded-in nose bridge provides uncompromised comfort and fit.
- ✓ Single-piece lens that will fit most faces.

>> **Conformity**

This product has been tested according to the following European Standards:

- ✓ **EN 166: 2001.** Personal eye-protection. Specifications.
- ✓ **EN 170: 2002.** Personal eye-protection. Ultraviolet filters. Transmittance requirements and recommended use.

It complies with the European **Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). **Category II.** EU type examination certificate (**module B**) issued by **BSI** (Netherlands). Notified body **n°2797**.

Download the EU declaration of conformity on: <http://docs.singer.fr>



Mechanical protection (EN166)	Symbole FT	Impact resistant against high speed particles at high temperatures (corresponds to the impact of a steel ball with a diameter of 6 mm and a minimum mass of 0.86 g launched at 45 m/s).
Optical quality (EN166)	Symbole 1	Class 1: continuous works (better quality).
Scale number (EN170)	Symbole 2C-1.2	<p>Colour perception: not impaired</p> <p>Typical application: for use with sources that emit UV radiation predominantly at wavelengths < 313 nm and when glare is not an important factor.</p> <p>This applies to UVC and most UVB radiation ^(b).</p> <p>Typical source ^(a): Low pressure mercury vapour lamps, such as those used to stimulate fluorescent or "black lights", actinic and germicidal lamps.</p> <p>(a) The example given for typical source is for general guidance.</p> <p>(b) The wavelengths of these bands are recommended by IEC (that is UVB 280 nm to 315 nm & 100 nm to 280 nm for UVC).</p>

Your distributor **SINGER® SAFETY**

