

PW65 - BizWeld Plus Welding Helmet

Collection: Welding

Range: Flame Resistant

Product information

Auto-darkening welding helmet, which switch from light to dark state when the welding activity starts. Light state is DIN 4; Dark state is adjustable from DIN 9 to DIN 13 using the external knob. Response time from light to dark state is 0.04 milliseconds; return from dark to clear state in 0.03-0.04 sec. Power is supplied by solar cells and 2 built-in lithium batteries offer power back-up for longer service life and no need of replacement batteries.

Standards

EN 166 (1 S)
EN 175 (F)
EN 379 (4 / 9-13 ; 1/1/1/2)
CE

Welding

Flame Resistant

This industry leading range provides multi standard protection for hazardous environments. These state of the art products are the result of years of experience combined with advanced technology and market research. Commitment to the health, safety and comfort of the wearer can be seen in the wide range of products suitable for all climates and end uses.

Features

- CE certified
- Wheel ratchet size adjustment for easy fitting
- Solar cell power and two built-in lithium back-up batteries. Working time over 5000 hours
- Auto-darkening, switches from light to dark when the welding process starts
- Suitable for a wide range of applications
- Suitable to be worn with disposable respirators
- Retail box which aids presentation for retail sales



Available colours

	Short	Reg	Tall	XTall
Black				

PORTWEST®

PRODUCT SPECIFICATION & TECHNICAL DATA

PW65 - BizWeld Plus Welding Helmet

Commodity Code: 9004901000

Test House

Din CERTCO (Notified Body No.: 0196)

Prufzentrum Augenschutz TillystraBe 2

90431, Germany

Cert No: C5465PW/R0 (PW65H welding face shield)

Din CERTCO (Notified Body No.: 0196)

Prufzentrum Augenschutz TillystraBe 2

90431, Germany

Cert No: C5466PW/R0 (PW65F Automatic Welding Filter)

Din CERTCO (Notified Body No.: 0196)

Prufzentrum Augenschutz TillystraBe 2

90431, Germany

Cert No: C5467PW/R0 (PW66 outer protective lens)

Item	Colour	Len	Wid	Hgt	Weight (Kg)	Cubic (m ³)	EAN13	DUN14
PW65BKR	Black	65.0	45.0	39.0	1.2200	0.1141	5036108255566	15036108744470